# Beta® 56A Supercardioid Dynamic Instrument Microphone

#### Overview

The Shure Beta 56A dynamic microphone has a frequency response specifically tailored for drums and instruments. An extremely uniform supercardioid pattern provides high gain-before-feedback and excellent rejection of unwanted noise. An integrated swivel-mount with XLR connector simplifies mounting and adjustments.

### Features

- Premier live performance microphone with Shure quality, ruggedness, and reliability
  Uniform supercardioid pick-up pattern for maximum gain before feedback and superior rejection of off-axis sound
  Tailored frequency response specifically shaped for drums, amplified instruments and horns
- •
- Neodymium magnet for greater sensitivity and higher output
- Advanced pneumatic shock mount system that minimizes transmission of mechanical noise and vibration
- Dent-resistant, steel mesh grille and enamel coated die-cast metal construction resist wear and abuse
  Built-in stand adapter with dynamic locking system and XLR connector simplifies setup and provides greater flexibility

2500 Hz

---- 6300 Hz ---- 10000 Hz

• Compact design reduces stage clutter

#### Available Models

BETA 56A	Supercardioid Swivel-mount Dynamic Microphone with high-output Neodymium Element, Vocal or Instrument



Beta 56A

#### **Specifications**

Cartridge Type	Dynamic (moving coil)	
Frequency Response	50 to 16,000 Hz	
Polar Pattern	Supercardioid	
Output Impedance	150 Ω	
Sensitivity (at 1kHz, open circuit voltage)	–51 dBV/Pa (2.8 mV) 1 Pascal=94 dB SPL	
Polarity	Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3	
Weight	Net: 0.468 lg (1.6 lbs)	
Connector	Three-pin professional audio (XLR), male	
	Thee-pin processional additio (XER), male	

## **Accessories and Replacement Parts**

RK320	Replacement grille	R174	Replacement cartridge
A1WS	Microphone windscreen	A56D	Drum microphone mount



**Frequency Response** 





www.shure.com