Product Specifications

PGA56 Cardioid Dynamic Snare/Tom Microphone

Overview

The PGA56 Cardioid Dynamic Snare/Tom Microphone is a professional quality microphone with highly durable design and construction that delivers excellent sound. Featuring a swivel joint with a quick release latch for fast and flexible positioning, the PGA56 is ideal for close-mic snare drum, tom and percussion applications.

Features

- Tailored microphone cartridge design for clear reproduction of sound source
- Swivel joint with quick release latch with a design similar to bicycle component-locking technology for extremely quick and easy positioning.
- Cardioid polar pattern picks up audio from the source while rejecting unwanted noise Updated industrial design with black metallic finish and grille for unobtrusive visual presence
- Drum mount included for quick attachment to drum rims, no additional mic stand required
- Available with and without XLR Cable for flexibility in gear choice –With 15 ft (4.6 m) XLR-XLR cable •
- -Without cable
- Zipper pouch included for additional protection during storage or transport
- Legendary Shure quality design and construction for exceptional performance in rigorous environments

Product Specifications

ions	
Dynamic (moving coil)	
50 to 15,000 Hz	
Cardioid	
200 Ω	
-57 dBV/Pa (1.45 mV) 1 Pa=94 dB SPL	
Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3	
287 g (10.12 oz)	PGA 56
Three-pin professional audio (XLR), male	
-20 to 165 °F (-29 to 74 °C)	
0 to 95%	
	Dynamic (moving coil) 50 to 15,000 Hz Cardioid 200 Ω -57 dBV/Pa (1.45 mV) 1 Pa=94 dB SPL Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3 287 g (10.12 oz) Three-pin professional audio (XLR), male -20 to 165 °F (-29 to 74 °C)

Available SKUs

PGA56-LC	Microphone, drum rim mount, stand adapter, and pouch (Less cable)
PGA56-XLR	Microphone, drum rim mount, stand adapter, pouch and 15 ft (4.6 m) XLR-to-XLR cable

Accessories

AP56DM	Break-resistant drum microphone mount	
31A1856	5/8* to 3/8* thread adapter	
C25J	25 ft (7.6 m) XLR-to-XLR cable	
RPMP56G	Replacement PGA56 black mesh grille	

Polar Pattern

Frequency Response





